



IABOK Wireless Intruder Alarm System

deter | detect | monitor | respond™

- * 100% wireless configuration
- * Convenient operation by remote control
- * 1,000,000 inlet RF pin sets maintains high reliability
- * Simple accessory expansion by automatic recoding
- * Late-night mute remote control
- * Remote control realizes detection by areas
- * On-site high-loudness deterring alarm
- * Automatic dialing of 8 pre-set phone numbers
- * Alarming detection area cue tone for remote monitoring by telephone
- * Digital high-fidelity voice message recording, automatic replaying
- * Phone line cut and damage alarming
- * Remote Arm / Disarm setup or siren triggering by telephone
- * Active or passive remote monitoring of the site via telephone

- * E2PROM information protection, power cut won't cause damages to data
- * Automatic switch between AC and DC ensures uninterrupted operation of the system
- * Expandable RF relay module enables the activation of other RF accessories after alarming
- * Standard cable alarming signal interface
- * Compatible with computerized community alarm processing center, smart community alarming network may be established
- * Timing arm/disarm by remote control
- * To achieve "full arm", "part arm", "timing switch on/off" and "emergent calling" by quick button on the panel.
- * Compatible with MICROVISION CID+PRO, ADEMCO Contact ID Communication Protocol.
- * Built-in high precision clock chip, to ensure the veracity of 24H timed "arm" and "disarm" function.



Specification:

Alarm Communication Mode	Dial through PTSN
Alarm Communication Protocol	MICROVISION CID+PRO, ADEMCO Contact ID
Zone Number	6 wireless zone + 1x24H zone
Programming Mode	On the control panel
Alarm Telephone Number Could Be Stored	8
Arm / Disarm Mode	Remote control or remote control via telephone or timed setup on the control panel
Alarm Message Recording	10 seconds
Wireless Receiving	315MHz (433MHz Option) by auto-recoding
RF Code Combination	1,000,000 non-repeating combinations, effectively reducing repetition rate.
Allowed Amount Of Expandable Wireless Accessories	60
If Support Wireless Siren	Yes
If Support Remote Our Recording	Yes
Siren Current (Max)	450mA
Operation Temperature	-10°C-50°C
Operation Humidity	<90%
Power Supply	DC 12V/500mA
External Backup Battery	UPS-12V (maintenance-free uninterrupted backup supply)
Installation	On the wall or desktop
Control Panel Material	ABS plastic
Control Panel Size	159 X 100 X 33mm