



Alarm System

deter | detect | monitor | respond™

MD55 Wireless Shutter Door Sensor



- * For shutter door use only
- * Aluminum alloy material can work in vile environment
- * Stainless steel loricae cable enhances the security and reliability
- * 360° rotatable antenna
- * Low power LED indication
- * Transmitting distance: >300m (open area)

MD03 Wireless Iron Door Sensor



- * For iron door use only
- * Stainless steel loricae cable enhances the security and reliability
- * 360° rotatable antenna
- * Low power LED indication
- * Transmitting distance: >300m (open area)

VIB70 Wireless Vibration Detector



- * Vibration alarm
- * Low power LED indicator
- * Anti RFI/EMI interference
- * Detection area: 1.5m
- * Transmitting distance: >150m (open area)

GLB45 Wireless Glass Break Detector



- * Build-in microprocessor and high quality microphone
- * 360° all-sides protection
- * Wall or ceiling mounted
- * Advanced static and instantaneous protection
- * Sensitivity optional
- * Anti-RFI/EMI interference, reduce the false alarm
- * Detection area: 360° / 6m
- * Transmitting distance: >300m (open area)
- * Power supply: 12V/500mA adapter, UPS-12V power supply optional

PM52 Wireless P.I.R. Motion Detector



- * Built-in Microprocessor
- * Auto temperature compensation
- * Low power LED indication
- * Anti-RFI/EMI interference
- * Detection distance: 8m
- * Detection angle: 110°
- * Power supply: 9V battery X 1
- * Transmitting distance: >150m (open area)